

NOTES:

- CONSTRUCTION SHALL CONFORM TO THESE REQUIREMENTS EXCEPT AS OTHERWISE DIRECTED BY THE COUNTY ENGINEER.
- 2. R1=ANCHOR BOLT DIAMETER DIMENSION. RADIUS AND BOLT PATTERN TO SUIT POLE BASE USED.
- 3. IN AREAS WHERE CONCRETE SIDEWALKS WILL BE POURED AFTER THE POLE FOUNDATION IS INSTALLED, POUR FOUNDATION TO BOTTOM ELEVATION OF SIDEWALK. IN AREAS WITHOUT CONCRETE AROUND FOOTING, CONSTRUCT A 2'x2' CONCRETE PAD (4" THICK).
- 4. FOUNDATION BOLTS SHALL NOT BE CUT OFF FOR ANY REASON. EXTENSION COUPLERS SHALL NOT BE PERMITTED.
- 5. LEVELING OF BASE SHALL CONFORM TO THE REQUIREMENTS OF STANDARD DRAWING NO. 620.

COUNTY OF SONOMA

DEPARTMENT OF TRANSPORTATION

AND PUBLIC WORKS

BASE DETAIL STANDARD STREET LIGHT POLE

	REVISED:
APPROVED BY: JH	scale: drawing no. 618