

- ULTIMATE EDGE OF PAVEMENT; CONSULT
 BIKE + PED PLAN TO ACCOUNT FOR CLASS
 II BIKE LANES.
- (2) EXISTING EDGE OF PAVEMENT.
- (3) CENTERLINE OF ROAD.
- 4 TAPER 10:1 FROM EXISTING EDGE OF PAVEMENT TO BEGINNING OF ACCESS CURVE (B.C.) AT THE INTERSECTION OF THE ULTIMATE EDGE OF PAVEMENT OR MINIMUM NEW PAVEMENT DESCRIBED BELOW.

FOR VERY LOW VOLUME COUNTY ROADS (LESS THAT 400 ADT), 4:1 TAPER CAN BE USED IF SIGHT DISTANCE REQUIREMENTS ARE ADEQUATE.

- (5A) SIGHT LINE: UNOBSTRUCTED VIEW FROM A POINT 14 FT Min, OUTWARD FROM EDGE OF TRAVELED WAY AND 3.5' ABOVE FINISHED SURFACE.
- THE SIGHT LINE LENGTH SHALL BE SUFFICIENT TO ALLOW FOR THE MINIMUM STOPPING SIGHT DISTANCE CORRESPONDING TO THE SPEED TRAVELED ON THE INTERSECTING ROADWAY PER THE TABLE BELOW.
- 6 PROJECTION OF ULTIMATE EDGE OF PAVEMENT ACROSS ACCESS.

R=RADIUS OF CURVE CONNECTING ACCESS ROAD WITH COUNTY ROAD.

R=48' MIN. FOR COMMERCIAL DRIVEWAY WITH 8' MIN. NEW PAVEMENT AT BC IF NO ULTIMATE E.P. IS DESIGNATED BY GENERAL PLAN.

R=25' MIN. FOR PRIVATE RD. AND PRIVATE DWY. (DWY. CAN BE LESS WITH APPROVED EXCEPTION FROM SONOMA COUNTY DEPT. OF FIRE SERVICES) WITH 6' MIN. NEW PAVEMENT AT BC IF NO ULTIMATE E.P. IS DESIGNATED BY GENERAL PLAN.

AASHTO SIGHT DISTANCE STANDARDS
DESIGN SPEED STOPPING
(MPH) DISTANCE (FT)
20 115
25 155
30 200
35 250
40
45
50 425
55 495

COUNTY OF SONOMA

DEPARTMENT OF TRANSPORTATION

AND PUBLIC WORKS

RURAL COUNTY ROAD
DRIVEWAY AND PRIVATE
ROAD INTERSECTIONS

·): MAR 2021
APPROVED BY:	SCALE:	drawing no.
JH	NONE	812